

MAR 20 2007

Appl. No. 10/800,371
Substitute Amdt. dated March 20, 2007
Reply to Office Action of December 26, 2006

PATENT

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) An apparatus for processing a supervisory signal for optical network applications, the apparatus comprising:
 - a subcarrier transmission system configured to receive a first supervisory signal and output a second supervisory signal;
 - an electrical-to-optical conversion system configured to receive the second supervisory signal and a first data signal and output a first optical signal;
 - an optical-to-electrical conversion system configured to receive the first optical signal and output a first electrical signal and a second data signal;
 - a subcarrier reception system configured to receive the first electrical signal and output a third supervisory signal;
 - wherein the second supervisory signal is associated with a first subcarrier frequency;
 - wherein the first data signal is associated with a first data bandwidth, the first data bandwidth including a first data frequency, at the first data frequency a power density of the first data signal substantially equal to zero;
 - wherein a ratio of the first subcarrier frequency to the first data frequency ranges from 0.8 to 1;
 - wherein the first optical signal is associated with a perturbation to the first data signal, the perturbation being smaller than or equal to 1 dB;
 - wherein the first optical signal is associated with a signal-to-noise ratio for the second supervisory signal ~~related to the first supervisory signal~~, the signal-to-noise ratio for the second supervisory signal being larger than or equal to 20 dB;
 - wherein the first supervisory signal is associated with a first subcarrier data rate larger than 1 Mbps.

Appl. No. 10/800,371
Substitute Amdt. dated March 20, 2007
Reply to Office Action of December 26, 2006

PATENT

2. (Original) The apparatus of claim 1 wherein the first subcarrier signal is associated with the first subcarrier data rate larger than 5 Mbps.

3. (Canceled)

4. (Original) The apparatus of claim 1 wherein the first data frequency is a maximum frequency associated with the first data bandwidth.

5. (Original) The apparatus of claim 4 wherein the first data frequency is substantially equal to 2.5 GHz and the first subcarrier frequency is substantially equal to 2.4 GHz.

6. (Original) The apparatus of claim 5 wherein the first data signal is associated with a non-return to zero format and a first data rate substantially equal to or smaller than 2.5 gigabits per second.

7.-18. (Canceled)

19. (Currently Amended) The method of claim 18A method for processing a supervisory signal for optical network applications, the method comprising:

receiving a first supervisory signal;

processing information associated with the first supervisory signal;

outputting a second supervisory signal based on at least information associated with the first supervisory signal;

receiving the second supervisory signal and a first data signal;

processing information associated with the second supervisory signal and the first data signal;

outputting a first optical signal based on at least information associated with the second supervisory signal and the first data signal;

receiving the first optical signal;

Appl. No. 10/800,371
Substitute Amdt. dated March 20, 2007
Reply to Office Action of December 26, 2006

PATENT

processing information associated with the first optical signal;
outputting a first electrical signal and a second data signal based on at least
information associated with the first optical signal;

receiving the first electrical signal;

processing information associated with the first electrical signal;

outputting a third supervisory signal;

wherein:

the second supervisory signal is associated with a first subcarrier
frequency;

the first data signal is associated with a first data bandwidth, the first data
bandwidth including a first data frequency, at the first data frequency a power density of
the first data signal substantially equal to zero;

a ratio of the first subcarrier frequency to the first data frequency ranges
from 0.8 to 1;

the first data frequency is a maximum frequency associated with the first
data bandwidth;

the first data frequency is substantially equal to 2.5 GHz and the first
subcarrier frequency is substantially equal to 2.4 GHz;

the first data signal is associated with a non-return to zero format and a
first data rate substantially equal to or smaller than 2.5 gigabits per second;

wherein the first optical signal is associated with a perturbation related to
the first data signal, the perturbation being smaller than or equal to 1 dB, the first optical
signal is associated with a signal-to-noise ratio for the second supervisory signal related to
the first supervisory signal, the signal-to-noise ratio for the second supervisory signal
being larger than or equal to 20 dB.

20. (Original) The method of claim 19 wherein the first supervisory signal is associated with a first supervisory data rate larger than 1 Mbps.

Appl. No. 10/800,371
Substitute Amdt. dated March 20, 2007
Reply to Office Action of December 26, 2006

PATENT

21. (Original) The apparatus of claim 20 wherein the first supervisory data rate is about 5 Mbps.

22.-30. (Canceled)